

# A Note on an Inferentialist Approach to Resource Semantics

Alexander V. Gheorghiu<sup>1</sup>    Tao Gu<sup>1</sup>    David J. Pym<sup>1,2,3</sup>

{alexander.gheorghiu.19, tao.gu.18, d.pym}@ucl.ac.uk

A central concept within informatics is that of a *distributed system* (Coulouris et al., 2011). From the systems modelling perspective, with a little abstraction, one can think of a distributed system as comprising delimited collections of interconnected component systems (Collinson et al., 2012; Caulfield and Pym, 2015). These systems ultimately comprise interconnected *locations*, at which are situated *resources*, relative to which *processes* execute — consuming, creating, moving, combining, and otherwise manipulating resources as they evolve, so delivering the system’s services. This broad definition applies across the many complex socio-economic-technical systems that define and support our world including physical and organizational infrastructure (e.g., city roads, management structures, etc.), telecommunication networks (e.g., the world wide web), and real-time process control systems (e.g., aircraft control systems).

An important use of logic is to represent, understand, and reason about such systems; this determines the field of *logical systems modelling*. To this end, one requires an interpretation of logical formulae in terms of the resources and states of the system; such an interpretation is called a *resource semantics* of the logic. We propose the following encompassing definition:

*A resource semantics for a system of logic is an interpretation of its formulae as assertions about states of processes and is expressed in terms of the resources that are manipulated by those processes.*

There is no intended restriction on the assertions that are to be included in the scope of this definition and assertions may refer not only to ground states but may also be ‘higher-order’ statements about state transitions. Moreover, the *manipulation* of resources by the system’s processes is general and includes, *inter alia*, consuming/using resources, creating resources, copying/deleting resources, and moving resources between locations.

There are, perhaps, two canonical examples of resource interpretations of logics that merit discussion, the *number-of-uses* reading of *Linear Logic* (LL) (Girard, 1987) and the *sharing/separation* reading of *the logic of Bunched Implications* (BI) (O’Hearn and Pym, 1999). While both are applicable to systems modelling, these two readings work in different ways and are related to different ways of doing the modelling. The number-of-uses reading (Lafont, 1993; Hoare, 1985) for LL concerns the dynamics of the system: formulae denote processes and resources themselves. Note, it is available only through LL’s proof theory, and is not reflected in LL’s truth-functional semantics (Girard, 1995). Meanwhile, the sharing/separation reading (Pym, 2019) of BI concerns the composition and state of the system; this is best exemplified by its essential place in *program verification* — see, for example, the use of *Separation Logic* (Reynolds, 2002). It proceeds through its (ordered-monoidal/relational) model-theoretic semantics of BI.

Both readings are useful, but they are individually limited for systems modelling: sharing/separation expresses the *structure* of distributed systems, and number-of-uses expresses the *dynamics* of the resources involved. Also, they operate in completely different paradigms: number-of-uses proceeds from LL’s proof theory, while sharing/separation proceeds from the semantics of BI. We suggest that *proof-theoretic semantics* (P-tS) (Schroeder-Heister, 2018) offers a unified framework for resource semantics able to express both parts of a distributed system.

---

<sup>1</sup>Department of Computer Science, University College London, London WC1E 6BT, UK

<sup>2</sup>Department of Philosophy Science, University College London, London WC1E 6BT, UK

<sup>3</sup>Institute of Philosophy, University of London, London WC1E 7HU, UK

In the semantic paradigm of P-tS, *inferentialism*, meaning emerges from rules of inference (Brandom, 2000). This stands in contrast to, for example, *denotationalism*, wherein the meaning of logical structures is grounded in reference to abstract algebraic structures, as in model-theoretic semantics. Much of the groundwork for P-tS has been provided by Prawitz (2006 [1965]), Dummett (1991), Schroeder-Heister (2006), and Piecha and Schroeder-Heister (2019).

Recently, Gheorghiu et al. (2023) and Buzoku (2024) have provided P-tS for (intuitionistic) LL, and Gu et al. (2024) have provided P-tS for BI, all building on essential work by Sandqvist (2015). Relative to these results, Gheorghiu et al. (2024) have initiated an inferentialist account of resource semantics that uniformly expresses both number-of-uses readings and sharing/separation interpretations of the logics. Moreover, they have illustrated its application to both modelling the security architecture of an airport and to multi-factor authentication.

These semantics are all given by an inductively defined judgment relation called *support* such that transmission of validity is defined as follows:

$$\Gamma \Vdash_{\mathcal{B}}^{S(\cdot)} \varphi \quad \text{iff} \quad \forall \mathcal{C} \supseteq \mathcal{B}, \forall U \in \mathbb{R}(\mathbb{A}), \text{ if } \Vdash_{\mathcal{C}}^U \Gamma, \text{ then } \Vdash_{\mathcal{C}}^{S(U)} \varphi \quad (\text{Gen-Inf})$$

Let us spell out each ingredient of (Gen-Inf) and their roles in the resource semantics, which describes the execution of certain policy in a system:

- $\varphi$  specifies an assertion describing (a possible state of) the system
- $\Gamma$  specifies a policy describing the executions of a system’s processes
- $\mathbb{R}(\mathbb{A})$  is some concept of atomic resource
- $S(\cdot)$  is some contextual atomic resource — that is, whenever  $S(\cdot)$  is combined with some atomic resource in  $U \in \mathbb{R}(\mathbb{A})$ , it returns a ‘richer’ atomic resource  $S(U)$
- $\mathcal{B}, \mathcal{C}$  are ‘bases’ (a basic concept in P-tS) and *model* the policy governing the system described by the assertions.

Putting these all together, the support judgement  $\Gamma \Vdash_{\mathcal{B}}^{S(\cdot)} \varphi$  says that, if policy  $\Gamma$  were to be executed with contextual resource  $S(\cdot)$  based on the model  $\mathcal{B}$ , then the result state would satisfy  $\varphi$ . (Gen-Inf) explains how such execution is triggered: for arbitrary model  $\mathcal{C}$  that extends  $\mathcal{B}$ , if policy  $\Gamma$  is met in model  $\mathcal{C}$  using some resource  $U$ , then  $\Gamma$  could be executed, and the resulting state — which consumes  $U$  in the available contextual resource  $S(\cdot)$  — satisfies  $\varphi$ . This summarizes an inferentialist approach to resource semantics.

Distributed systems play a crucial role in society and logic is a primary tool for representing, understanding, and reasoning about them. Adopting logical inferentialism, particularly through recent advancements in the proof-theoretic semantics of substructural logics, offers a unified approach for logical modelling of systems. This approach not only encapsulates existing methodologies but also introduces novel, refined features, enhancing our capabilities in this domain.

## References

- Brandom, R. (2000), *Articulating Reasons: An Introduction to Inferentialism*, Harvard University Press.
- Buzoku, Y. (2024), ‘A Proof-theoretic Semantics for Intuitionistic Linear Logic’, arXiv:2402.01982. Submitted.
- Caulfield, T. and Pym, D. (2015), Modelling and simulating systems security policy, in Proc. 8th SIMUTools ’15, ICST, 9–18.
- Collinson, M., Monahan, B. and Pym, D. (2012), *A Discipline of Mathematical Systems Modelling*, College Publications.
- Coulouris, G., Dollimore, J., Kindberg, T. and Blair, G. (2011), *Distributed Systems: Concepts and Design*, 5th edn, Addison-Wesley.
- Dummett, M. (1991), *The Logical Basis of Metaphysics*, Harvard University Press.
- Gheorghiu, A. V., Gu, T. and Pym, D. J. (2023), Proof-theoretic semantics for intuitionistic multiplicative linear logic, in R. Ramanayake and J. Urban, eds, ‘Automated Reasoning with Analytic Tableaux and Related Methods — TABLEAUX’, Springer, pp. 367–385.
- Gheorghiu, A. V., Gu, T. and Pym, D. J. (2024), ‘Inferentialist resource semantics’, arXiv:2402.09217.
- Girard, J.-Y. (1987), ‘Linear logic’, *Theoretical computer science* **50**(1), 1–101.
- Girard, J.-Y. (1995), Linear logic: its syntax and semantics, in ‘Advances in Linear Logic’, LMS Lecture Notes, CUP, 1–42.
- Gu, T., Gheorghiu, A. V. and Pym, D. J. (2024), ‘Proof-theoretic-semantics for the Logic of Bunched Implications’, arXiv:2311.16719.
- Hoare, C. A. R. (1985), *Communicating Sequential Processes*, Prentice-Hall International.
- Lafont, Y. (1993), ‘Introduction to linear logic’. Lecture notes from TEMPUS Summer School on Algebraic and Categorical Methods in Computer Science, Brno, Czech Republic.
- O’Hearn, P. W. and Pym, D. J. (1999), ‘The Logic of Bunched Implications’, *Bulletin of Symbolic Logic* **5**(2), 215–244.
- Piecha, T. and Schroeder-Heister, P. (2019), ‘Incompleteness of Intuitionistic Propositional Logic with Respect to Proof-theoretic Semantics’, *Studia Logica* **107**(1), 233–246.
- Prawitz, D. (2006 [1965]), *Natural Deduction: A Proof-theoretical Study*, Courier Dover Publications.
- Pym, D. J. (2019), ‘Resource Semantics: Logic as a Modelling Technology’, *ACM SIGLOG News* **6**(2), 5–41.
- Reynolds, J. C. (2002), Separation Logic: A Logic for Shared Mutable Data Structures, in Proc. LICS 2002, IEEE, 55–74.
- Sandqvist, T. (2015), ‘Base-extension Semantics for Intuitionistic Sentential Logic’, *Logic Journal of the IGPL* **23**(5), 719–731.
- Schroeder-Heister, P. (2006), ‘Validity Concepts in Proof-theoretic Semantics’, *Synthese* **148**(3), 525–571.
- Schroeder-Heister, P. (2018), Proof-Theoretic Semantics, in E. N. Zalta, ed., ‘The Stanford Encyclopedia of Philosophy’, Spring 2018 edn.